

Selection guide - Section D

Rocker and paddle switches

							
Series	SMT TR	TR	S-SR	AS	MT	7000	FM
Page	D-2	D-4	D-9	D-19	D22	D-24	D-30
Poles	1	1,2	1,2	1	1	1,2	1
Maximum ratings	0,4VA 20V AC/DC	0,5A 48V AC/DC	(2A 250VAC)* 4A 30VDC	(2A 250VAC)*	4A 30VDC	(3A 250VAC)* 4A 30VDC	(10A 250VAC)*
Illuminated							X
Mounting options							
Horizontal SMT	X						
Vertical Through hole		X	X	X	X	X	X
Horizontal Through hole		X	X			X	
Vert. right angle TH		X	X			X	
Snap-in			X	X		X	X
Rear mounting			X			X	
Panel cut-out				18,65X8,9	Ø 17,65		19,2x12,9
Terminal options							
PCB	X	X	X	X	X	X	X
Solder lugs			X	X	X	X	X
Quick-connect							X
Sealing	Process sealed	Process sealed	Process sealed	No	No	No	Optional boot

						() * See applicable approvals
Series	2600	KR	KL	KI	KG	
Page	D-33	D-41	D-50	D-59	D-61	
Poles	1,2	1,2	1,2		1,2	
Maximum ratings	(16A 250VAC)*	10A 24VDC	10A 24VDC	24VDC	(12A 250VAC)* 15A 12VDC	
Illuminated	X	X	X	X	X	
Mounting options						
Snap-in	X	X	X	X	X	
Panel cut-out	30 x 22	36,8 X 21,08	36,8 X 21,08	36,8 X 21,08	36,8 X 21,08	
Terminal options						
Solder lugs	X	X	X	X	X	
Quick-connect	X	X	X	X	X	
Screw	X	X	X		X	
Sealing	Optional boot	IP68	IP68	IP68	IP65	