









Selection guide - Section C

Tact switches

								
Series	D162	PHAP3390 PHAP3391	PHAP3380	PHAP3371 PHAP3372 PHAP3373 PHAP3374	PHAP3378	PHAP3361	PHAP3355	PHAP3366 PHAP3365
Page	C 2	C-4	C-5	C-6	C-8	C-9	C-9	C-10
Type (SMT/Through hole)	SMT	SMT	SMT	SMT	SMT	SMT	SMT	SMT
Contact	N.O.	N.O.	N.O.	N.O.	N.C.	N.O.	N.O.	N.O.
Case format	6x6mm	4,2x4,2mm	6x6mm	6,2x6,2mm	7,6x7,6mm	6x3,5mm	6x3,5mm	6,1x3,7mm
Button height from PCB	3,96mm	1,5mm	1,6mm	2,6 to 3,4mm	4,3mm	4,3 and 5mm	1,8mm	2,5mm
Grounding tab	Yes	-	Yes	Yes	-	-	Yes	-
Packaging	T/R	T/R - Bags	T/R - Bags	T/R - Bags	T/R	T/R - Bags	T/R	T/R
Maximum ratings	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC
Mounting options								
SMT	X	X	X	X	X	X		X
Right angle SMT							X	
								
Series	PHAP3368	PHAP3305	PHAP3362 PHAP3363	PHAP3301 to PHAP3308	PHAP3307	PHAP3350 PHAP3351 PHAP3352	PHAP3353	PHAP3320 PHAP3321
Page	C-11	C-11	C-12	C-13	C-14	C-15	C-15	C-16
Type (SMT/Through hole)	SMT	SMT	Through hole	Through hole	Through hole	Through hole	Through hole	Through hole
Contact	N.O.	N.O.	N.O.	N.O.	N.O.	N.O.	N.O.	N.O.
Case format	6x6mm	6x6mm	6x3,5mm	6x6mm	6,1x6,1mm	7,2x7,2mm	10x10mm	12x12mm
Button height from PCB	4,3 to 13mm	5,9mm	4,3 and 5mm	4,3 to 13mm	4,3 to 7mm	4,35 to 13mm	13mm	4,3 to 12mm
Grounding tab	-	Yes	-	Yes	-	Yes	-	Yes
Caps	Yes	-	-	Yes	-	-	-	Yes
Packaging	T/R - Bags	T/R	Bags	Bags	Tape	Bags	Bags	Bags
Process sealed						Yes	Yes	
Maximum ratings	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC	50mA 12VDC
Mounting options								
SMT	X							
Right angle SMT		X						
Through hole			X	X	X	X	X	X
Right angle Through hole			X	X		X		