

VIBRATION SENSORS

TE has spent more than 20 years designing and manufacturing accelerometers based on our proprietary Microelectromechanical System (MEMS), bonded gage and piezoelectric ceramic/film technologies. Voltage mode piezoelectric is the most popular accelerometer design due to its high level output and wide bandwidth. We offer voltage mode accelerometers in the traditional 3-wire or 2-wire (IEPE) configurations. Charge mode piezoelectric accelerometers measure shock and vibration in high temperature environments. In addition to its high temperature operating capability when used with a high quality charge amplifier, a charge mode accelerometer offers dynamic range scalability. To measure motion (velocity, displacement) accurately, an accelerometer or with DC response is required. Incorporating MEMS technologies and the latest analog and digital ASICs, our DC accelerometers offer high performance and exceptional value. All products are EAR99 and RoHS compliant.



MEMS DC ACCELEROMETERS

Embedded



MEAS 3022, 3028

Package	Pins or pads
Type	Board level
FS Range (g)	±2, 5, 10, 20, 50, 100, 200
Unique Features	<ul style="list-style-type: none"> • mV output • Gas damping • Pin or pad option
Accuracy	±0.5% non-linearity
Operating Temp.	-40°C to 125°C
Dimensions (mm)	22.86 x 15.24 x 5.33
Typical Applications	Vibration and shock monitoring, tilt applications, motion control, impact testing



MEAS 3052A, 3058A

Package	Pins or pads
Type	Board level
FS Range (g)	±2, 5, 10, 20, 50, 100
Unique Features	<ul style="list-style-type: none"> • Temperature compensated • Gas damping • Pin or pad option
Accuracy	±0.5% non-linearity
Operating Temp.	-40°C to 125°C
Dimensions (mm)	22.86 x 15.24 x 5.33
Typical Applications	Vibration and shock monitoring, tilt applications, motion control, impact testing



MEAS 3038

Package	SMD
Type	Board level
FS Range (g)	±50, 100, 200, 500, 2000, 6000
Unique Features	<ul style="list-style-type: none"> • Hermetically sealed • High over-range protection • Gas damping
Accuracy	±0.5% non-linearity
Operating Temp.	-54°C to 125°C
Dimensions (mm)	7.62 x 7.62 x 3.3
Typical Applications	Vibration and shock monitoring, embedded systems, shock testing, safe and arm



MEAS 3255A

Package	SMD
Type	Board level
FS Range (g)	±25, 50, 100, 250, 500
Unique Features	<ul style="list-style-type: none"> • Self test enabled • Gas damping • Bidirectional mounting
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 125°C
Dimensions (mm)	13.46 x 7.62 x 3.81
Typical Applications	Vibration and shock monitoring, aerospace testing, impact testing, transportation

PIEZOELECTRIC ACCELEROMETERS

Embedded Single Axis



MEAS 805, 805M1

Package	TO - 5
Type	Adhesive (Stud mount option)
FS Range (g)	±50, 500 / ±20, 200
Unique Features	<ul style="list-style-type: none"> • Hermetically sealed • Case grounded design • Bandwidth to 12 kHz
Accuracy	±1.0% non-linearity
Operating Temp.	-50°C to 100°C
Dimensions (mm)	Ø8.9 x 10.16
Typical Applications	Machine monitoring, data loggers, permanent structures



MEAS 808, 808M1

Package	TO - 8
Type	Adhesive (Stud mount option)
FS Range (g)	±10, 50 / ±4, 20
Unique Features	<ul style="list-style-type: none"> • Hermetically sealed • Case grounded design • Bandwidth to 8 kHz
Accuracy	±1.0% non-linearity
Operating Temp.	-50°C to 100°C
Dimensions (mm)	Ø15.2 x 16.6
Typical Applications	Machine monitoring, data loggers, embedded applications



MEAS 810M1

Package	Board level
Type	SMD
FS Range (g)	±25, 100
Unique Features	<ul style="list-style-type: none"> • Small size, low cost • Dynamic response • 6 kHz bandwidth
Accuracy	±2.0% non-linearity
Operating Temp.	-40°C to 125°C
Dimensions (mm)	12.70 x 15.24
Typical Applications	Data logging, impact detection



MEAS LDTC Family

Package	Piezo film elements with or without mass and pins
Type	Cantilever beam with vertical or horizontal pins
FS Range (g)	±10 (Typical)
Unique Features	<ul style="list-style-type: none"> • Very low cost • High sensitivity (1 V/g) • Ultra-low power (Self generating)
Accuracy	±20.0% (Typical)
Operating Temp.	-40°C to 70°C
Dimensions (mm)	19.05 x 6.35 x 6.35
Typical Applications	Wake-up switch, load imbalance, anti-theft devices, impact sensing, vital signs monitoring

PIEZOELECTRIC ACCELEROMETERS

Embedded Triaxial



MEAS 832, 832M1

Package	SMD
Type	Board mount
FS Range (g)	±25, 50, 100, 200, 500
Unique Features	<ul style="list-style-type: none"> • Low cost • Hermetically sealed • Piezo-ceramic
Accuracy	±2.0% non-linearity
Operating Temp.	-20°C to 80°C (832) -40°C to 125°C (832M1)
Dimensions (mm)	18.8 x 14.22 x 4.32
Typical Applications	Data logging, asset monitoring, impact monitoring



MEAS 834, 834M1

Package	SMD
Type	Board mount
FS Range (g)	±2000, 6000
Unique Features	<ul style="list-style-type: none"> • Low cost • Hermetically sealed • Piezo-ceramic
Accuracy	±2.0% non-linearity
Operating Temp.	-20°C to 80°C (834) -40°C to 125°C (834M1)
Dimensions (mm)	18.8 x 14.22 x 4.32
Typical Applications	Data logging, asset monitoring, impact monitoring

DC ACCELEROMETERS

Plug and Play, Unamplified



MEAS 40A, 40B

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±25, 100, 250, 500, 1000, 2000
Unique Features	<ul style="list-style-type: none"> • Critically damped • SAE J211 / 2570 compliant • Compact
Accuracy	±1.0% non-linearity
Operating Temp.	-20°C to 80°C
Dimensions (mm)	16.7 x 10.0 x 5.0
Typical Applications	In-dummy and pedestrian crash testing



MEAS 52F

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±50, 200, 500, 2000
Unique Features	<ul style="list-style-type: none"> • Low cost • Gas damping • Over-range stops
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 90°C
Dimensions (mm)	11.2 x 10.2 x 3.8
Typical Applications	Vibration and shock monitoring, shock testing, safety impact testing, side-impact testing



MEAS 52, 52M30

Package	Plastic / anodized aluminum
Type	Adhesive mount
FS Range (g)	±50, 200, 500, 2000
Unique Features	<ul style="list-style-type: none"> • Low cost • Gas damping • Over-range stops
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 90°C
Dimensions (mm)	9.65 x 4.83 x 3.3
Typical Applications	Vibration and shock monitoring, shock testing, safety impact testing, side-impact testing

DC ACCELEROMETERS

Plug and Play, Unamplified



MEAS 64B, 64C

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±50, 100, 200, 500, 2000, 6000
Unique Features	<ul style="list-style-type: none"> • SAE J211 / 2570 compliant • Flexible, rugged cable • Over-range stops
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 121°C
Dimensions (mm)	12.19 x 4.83 x 4.83
Typical Applications	In-dummy crash and impact testing



MEAS 58

Package	Anodized Aluminum
Type	Adhesive mount
FS Range (g)	±50, 100, 200, 500, 2000
Unique Features	<ul style="list-style-type: none"> • Low noise cable • Small package • Light weight
Accuracy	±1.0% non-linearity
Operating Temp.	-20°C to 85°C
Dimensions (mm)	14.0 x 6.35 x 6.35
Typical Applications	Crash testing, impact testing, off road testing



MEAS 1201, 1201F

Package	Anodized aluminum
Type	Adhesive / screw mount
FS Range (g)	±50, 100, 200, 500, 1000
Unique Features	<ul style="list-style-type: none"> • Small size • Flexible, rugged cable • Over-range stops
Accuracy	±1.0% non-linearity
Operating Temp.	-20°C to 85°C
Dimensions (mm)	8.89 x 8.89 x 9.4
Typical Applications	On-vehicle crash and impact testing, vibration and shock monitoring



MEAS 3801A

Package	Stainless steel
Type	Stud mount
FS Range (g)	±2, 10, 20, 50, 100, 200, 500, 2000
Unique Features	<ul style="list-style-type: none"> • Hermetically sealed sensor • Gas damping • 10,000 g over-range protection
Accuracy	±0.5% non-linearity
Operating Temp.	-54°C to 121°C
Dimensions (mm)	15.88 x 15.24
Typical Applications	Impact testing, structural testing, test and instrumentation, environmental testing



MEAS 3700

Package	Stainless steel
Type	Screw mount
FS Range (g)	±50, 200, 500, 2000, 6000
Unique Features	<ul style="list-style-type: none"> • No zero shift • mV output • 20,000 g over-range protection
Accuracy	±2.0% non-linearity
Operating Temp.	-54°C to 121°C
Dimensions (mm)	14.22 x 8.13 x 3.81
Typical Applications	Impact and shock testing, structural testing, drop testing, aerospace testing



MEAS EGAXT

Package	Stainless steel
Type	Adhesive / screw mount
FS Range (g)	±5 through 2500
Unique Features	<ul style="list-style-type: none"> • Sub-miniature • Lightweight • 10,000 g over-range protection
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 120°C
Dimensions (mm)	7.2 x 4.6 x 4.6
Typical Applications	Flight test and control, launch, crash, impact testing, robotics



MEAS EGCS-D0, EGCS-D1S

Package	Stainless steel
Type	Screw / stud mount
FS Range (g)	±5 through 10,000
Unique Features	<ul style="list-style-type: none"> • Rugged housing • Critically damped • 10,000 g over-range protection
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 120°C
Dimensions (mm)	D0: 19.05 x 19.05 x 7.62 D1S: 12.7 x 12.7 x 15.24
Typical Applications	General purpose, machine control, destructive testing, engine testing



MEAS EGCS-S425

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±50, 100, 250, 500, 1000, 2000
Unique Features	<ul style="list-style-type: none"> • Critically damped • Compact • Mechanical stops
Accuracy	±1.0% non-linearity
Operating Temp.	-20°C to 80°C
Dimensions (mm)	14.73 x 9.9 x 4.83
Typical Applications	Auto safety testing for side impact, on-vehicle, sled and in-dummy



MEAS EGCS-D5

Package	Stainless steel
Type	Screw mount
FS Range (g)	±50, 100, 250, 500, 1000, 2500, 5000, 10000
Unique Features	<ul style="list-style-type: none"> • Rugged design, miniature • Critically damped • In-line amplifier option
Accuracy	±1.0% non-linearity
Operating Temp.	-40°C to 100°C
Dimensions (mm)	14.2 x 12.7 x 5.6
Typical Applications	Impact and shock testing, drop testing, structural testing

DC ACCELEROMETERS

Plug and Play, Amplified



MEAS 4000A, 4001A

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±2, 5, 10, 20, 50, 100, 200
Unique Features	<ul style="list-style-type: none"> • Integral connector option • Gas damping • Low power
Accuracy	±1.0% non-linearity
Excitation Voltage	8 - 32 VDC
Operating Temp.	-20°C to 85°C
Dimensions (mm)	18.54 x 18.54 x 8.64
Typical Applications	Low frequency monitoring, transportation, vibration monitoring, motion control



MEAS 4602, 4604

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±2, 5, 10, 30, 50, 100, 200,
Unique Features	<ul style="list-style-type: none"> • Exceptional temp. compensation • High over-range • Hermetically sealed
Accuracy	±1.0% non-linearity
Excitation Voltage	8 - 36 VDC
Operating Temp.	-54°C to 125°C
Dimensions (mm)	21.08 x 21.59 x 7.62
Typical Applications	Flight testing on engines, flutter test, weapons development



MEAS 4610, 4610A

Package	Anodized aluminum
Type	Screw mount
FS Range (g)	±2, 10, 30, 50, 100, 200, 500
Unique Features	<ul style="list-style-type: none"> • Low noise ranges • Temperature compensation • High over-range • Hermetically sealed
Accuracy	±1.0% non-linearity
Excitation Voltage	8 - 36 VDC
Operating Temp.	-40°C to 115°C
Dimensions (mm)	21.59 x 25.4 x 7.62
Typical Applications	Rail motion control, modal analysis, flight test, structural test



MEAS 4801A

Package	Stainless steel
Type	Stud mount
FS Range (g)	±2, 10, 20, 50, 100, 200, 500, 2000
Unique Features	<ul style="list-style-type: none"> • Hermetically sealed sensor • Integral connector • Signal conditioned
Accuracy	±1.0% non-linearity
Excitation Voltage	8 - 36 VDC
Operating Temp.	-55°C to 125°C
Dimensions (mm)	13.33 x 20.83
Typical Applications	Impact testing, structural testing, test and instrumentation, environmental testing



MEAS 4807A

Package	Stainless steel
Type	Screw mount
FS Range (g)	±2, 5, 10, 20, 30, 50, 100, 200, 500
Unique Features	<ul style="list-style-type: none"> • Ultra low noise • Micro-g resolution • Hermetically sealed • Detachable cable
Accuracy	±1.0% non-linearity
Excitation Voltage	8 - 18 VDC
Operating Temp.	-55°C to 125°C
Dimensions (mm)	18.54 x 18.54 x 8.64
Typical Applications	Seismic, structural monitoring, flight testing, trains, machine control, road test



MEAS 4810A

Package	Stainless steel
Type	Screw mount
FS Range (g)	±2, 5, 10, 20, 30, 50, 100, 200
Unique Features	<ul style="list-style-type: none"> • UltraStable MEMS • Hermetically sealed • Signal conditioned
Accuracy	±1.0% non-linearity
Excitation Voltage	8 - 36 VDC
Operating Temp.	-55°C to 125°C
Dimensions (mm)	25.4 x 29.1 x 7.6
Typical Applications	Low frequency monitoring, road testing, motion analysis





DC ACCELEROMETERS

Plug and Play, Triaxial

	 MEAS EGAXT3	 MEAS 53/53A	 MEAS 68CM1	 MEAS 4630, 4630A	 MEAS 4020, 4030	 MEAS 606M1
Package	Stainless steel	Anodized aluminum	Stainless steel	Anodized aluminum	Molded plastic	Nitrile rubber pad
Type	Stud mount	Adhesive mount	Screw mount	Screw mount	Screw mount	Removable
FS Range (g)	±5 through 2500	±50, 200, 500, 2000	±500, 1000, 2000	±2, 5, 10, 30, 50, 100, 200, 500	±2, 6	±25
Unique Features	<ul style="list-style-type: none"> • Sub-miniature • Lightweight • 10,000 g over-range protection 	<ul style="list-style-type: none"> • Low cost • Gas damping • Low power 	<ul style="list-style-type: none"> • World SID • Gas damping • Low power 	<ul style="list-style-type: none"> • Low noise ranges • Temperature compensated • High over-range • Hermetically sealed 	<ul style="list-style-type: none"> • Low cost • Biaxial, with triaxial option • DC response • Rugged construction 	<ul style="list-style-type: none"> • 0.7 damping ratio • Triaxial, hermetic • Seat pad accelerometer • 606M2 IEPE option
Accuracy	±1.0% non-linearity	±1.0% non-linearity	±1.0% non-linearity	±1.0% non-linearity	±1.0% non-linearity	±1.0% non-linearity
Operating Temp.	-40°C to 120°C	-20°C to 85°C	-20°C to 85°C	-40°C to 115°C	-40°C to 85°C	-20°C to 85°C
Dimensions (mm)	12.7 x 12.7 x 12.7	18.29 x 13.21 x 7.11	12.7 x 12.7 x 12.7	26.16 x 26.16 x 23.37	71.2 x 40.0 x 15.2	199 x 4
Typical Applications	Flight test, crash, shock monitoring	Auto safety, passenger comfort, transportation, NVH analysis	Auto safety, in-dummy crash, on-vehicle crash	Road testing, motion control, structural testing	Structural monitoring, seismic array, bridge testing	Off road equipment, amusement rides, commercial aircraft







CHARGE MODE, PIEZOELECTRIC ACCELEROMETERS

Plug and Play

	 MEAS 7500A	 MEAS 7501A	 MEAS 7502A	 MEAS 7504A, 7505A	 MEAS 7514A	 MEAS 7531A
Package	Stainless steel	Titanium	Titanium	Stainless steel	Stainless steel	Titanium
Type	Center-hole mount	Center-hole mount	Adhesive mounting	Stud mount	Stud mounting	Adhesive mount
Sensitivity (pC/g)	20, 13, 7	5.6	1.8	5.6	100, 50, 30, 20, 13	1.8
Unique Features	<ul style="list-style-type: none"> • Single axis, shear mode • Hermetically sealed • Isolated mounting surface • Wide bandwidth 	<ul style="list-style-type: none"> • Single axis, shear mode • Hermetically sealed • Bandwidth to >15 kHz 	<ul style="list-style-type: none"> • Single axis, shear mode • Hermetically sealed • <1 g • Wide bandwidth 	<ul style="list-style-type: none"> • Single axis, shear mode • Top and side connector option • >15 kHz Bandwidth 	<ul style="list-style-type: none"> • Single axis, shear mode • >12 kHz bandwidth • High sensitivity 	<ul style="list-style-type: none"> • Triaxial, shear mode • Miniature, light weight • >10 kHz bandwidth
Operating Temp.	-73°C to 260°C	-73°C to 260°C	-73°C to 260°C	-73°C to 260°C	-73°C to 260°C	-73°C to 260°C
Dimensions (mm)	8.38 x 22.35	5.84 x 14.48	4.40 x 11.94	11.11 x 14.10 (7504A) 11.11 x 19.05 (7505A)	14.99 x 14.99	11.02 x 13.6 x 11.02
Typical Applications	Gearbox vibration monitoring, flight test, high temp. applications	Gearbox vibration monitoring, flight test, high temp. applications	Small structures monitoring, minimal mass loading, high temp. applications	Small structures monitoring, general purpose, high temp. applications	Low frequency vibration, general purpose, high temp. applications	High temp. applications, flight testing, structural monitoring

VOLTAGE MODE, PIEZOELECTRIC (IEPE) ACCELEROMETERS

Plug and Play

						
	MEAS 7100A, 7101A	MEAS 7102A	MEAS 7108A	MEAS 7104A, 7105A	MEAS 7131A, 7132A	MEAS 7120A, 7122A
Package	Stainless steel / titanium	Titanium	Stainless steel	Stainless steel	Titanium	Titanium
Type	Center-hole mount	Adhesive mount	Adhesive mounting	Stud mounting	Adhesive / stud mounting	Adhesive mounting
Sensitivity (mV/g)	100, 10, 5	100, 50, 20, 10, 5	100, 10	100, 50, 20, 10, 5	500, 100, 50, 10, 5, 2.5	100, 10
Unique Features	<ul style="list-style-type: none"> • Single axis, shear mode • Isolated mounting surface • Hermetically sealed • Wide bandwidth, >10 kHz 	<ul style="list-style-type: none"> • Single axis, shear mode • Wide bandwidth • <1 g weight 	<ul style="list-style-type: none"> • Single axis, shear mode • Wide bandwidth • Welded construction • Small size 	<ul style="list-style-type: none"> • Single axis, shear mode • Wide bandwidth • Top and side connector option 	<ul style="list-style-type: none"> • Triaxial, shear mode • >12 kHz bandwidth • 4-pin connector • Hermetically sealed 	<ul style="list-style-type: none"> • Single axis, shear mode • Miniature cube • 10 - 32 connector • Hermetically sealed
Operating Temp.	7100A: -55°C to 150°C 7101A: -55°C to 125°C	-55°C to +125°C	-55°C to 125°C	-55°C to 125°C	-55°C to 125°C	-55°C to 125°C
Dimensions (mm)	7100A: 9.9 x 22.35 7101A: 5.84 x 14.48	4.40 x 11.94	9.53 x 10.16	7104A: 11.11 x 14.10 7105A: 11.11 x 19.05	7131A: 11 x 11 x 11 7132A: 15.24 x 20.32 x 13.46	10.16 x 10.16 x 19.16
Typical Applications	Flight testing, general purpose, vibration monitoring	Small structures monitoring, minimal mass loading, general purpose testing	Vibration monitoring, modal testing, general purpose	General purpose IEPE accel, vibration monitoring, lab testing	General purpose, modal testing, vibration monitoring	Modal testing, vibration monitoring, small structures monitoring

VOLTAGE MODE, PIEZOELECTRIC ACCELEROMETERS

Plug and Play

						
	MEAS 8042	MEAS 8011, 8021-01	MEAS 8032-01	MEAS 8711-01	MEAS 8011, 8021-AR/AP	MEAS 8011, 8021-VR/VP
Package	Titanium	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Type	Stud mount	Stud / center-hole mount	Stud mount	Stud mount	Stud / center-hole mount	Stud / center-hole mount
Sensitivity (mV/g)	500, 100, 10	500, 100, 10	100, 10	1000, 500, 250, 100	4 - 20 mA RMS or peak	4 - 20 mA RMS or peak
Unique Features	<ul style="list-style-type: none"> • Industrial applications • Submersible • IP68, >100 meters • 16 kHz bandwidth 	<ul style="list-style-type: none"> • Industrial accelerometer • Case isolated, internal shielding • Reverse wiring protection • ±1.0% non-linearity 	<ul style="list-style-type: none"> • Industrial accelerometer • Case isolated, internal shielding • Low cost • Molded strain relief 	<ul style="list-style-type: none"> • Industrial accelerometer • Case isolated, internal shielding • Low cost 	<ul style="list-style-type: none"> • Industrial accelerometer • Case isolated, internal shielding • 50, 20, 10, 5 g ranges 	<ul style="list-style-type: none"> • Velocity transmitter • Case isolated, internal shielding • 0.5 to 5.0 in/sec
Operating Temp.	-20°C to 80°C	-55°C to 125°C	-55°C to 100°C	-55°C to +125°C	-40°C to 85°C	-40°C to 85°C
Dimensions (mm)	22.23 x 48.26	22.23 x 48.26	14.3 x 45.3	22.23 x 50.80	22.23 x 48.26	22.23 x 48.26
Typical Applications	Submersed pump monitoring, underwater research, gearbox monitoring	Industrial applications, machine monitoring, intrinsic safety	Industrial applications, machine monitoring	Industrial applications, machine monitoring, wind turbines	Industrial applications, machine monitoring, intrinsic safety	Industrial applications, machine monitoring, intrinsic safety

ELECTRONICS

Signal Conditioners



MEAS 121

Type Bench top
of Channels 3
Gain Range 0.001 to 9999
Unique Features

- Universal DC amplifier
- Low noise operation with auto-zero
- For bridge type sensors
- μ P controlled, programmable
- Low pass filter options

Dimensions (mm) 301 x 258 x 102
Typical Applications Instrumentation labs, test benches, R&D facilities



MEAS 130

Type In-line charge converter
of Channels 1
Gain Range 0.1, 1, 10
Unique Features

- Low noise
- Small package
- Wide bandwidth
- BNC male or female

Dimensions (mm) \varnothing 13.8 x 52.2
Typical Applications Instrumentation labs, high temperature testing PE accelerometer



MEAS 140/142

Type Auto-zero inline amplifier
of Channels 1
Gain Range 10, 25, 50, 100, 200, 500
Unique Features

- ± 1.5 mV auto-zero
- For bridge type sensor (140)
- For strain gage (142)
- Lowest noise
- 5 to 30 VDC excitation

Dimensions (mm) 56.9 x 25.4 x 12.7
Typical Applications Instrumentation labs, test benches, R&D facilities



MEAS 160

Type Bench top
of Channels 1
Gain Range 1, 10
Unique Features

- Economical IEPE power supply
- Portable, compact
- Rechargeable battery

Dimensions (mm) 3.95 x 2.83 x 1.58
Typical Applications Instrumentation



MEAS 161

Type Bench top
of Channels 4
Gain Range 0.001 to 999.9
Unique Features

- Charge and IEPE conditioner
- Sensitivity normalization
- LCD display
- Support IEEE 1451.4 TEDS
- 10 V peak linear output
- Selectable LP filter

Dimensions (mm) 310 x 180 x 115
Typical Applications Instrumentation labs, PE / IEPE sensors